



---

# SAFYBOX BRES

## MONOBLOCK INDUSTRIAL ENCLOSURES


---

ADVANTAGES AND CHARACTERISTICS.....3

SAFYBOX BRES MODELS.....11

- BRES           EMPTY ENCLOSURE - OPAQUE DOOR
- BRES-P       EMPTY ENCLOSURE - DOOR WITH TRANSPARENT WINDOW
- BRES-3L      EMPTY ENCLOSURE - OPAQUE DOOR AND TRIPLE LOCK WITH HANDLE
- BRES-P-3L   EMPTY ENCLOSURE - DOOR WITH TRANSPARENT WINDOW AND TRIPLE LOCK WITH HANDLE
- BRES-H       EMPTY ENCLOSURE - BRES HORIZONTAL POSITION






# INDEX



BASE PLATE.....	17	PACKING.....	41
MODULAR SWITCHGEAR FRAME (17,5mm) ..	19	GENERAL DATA.....	42
INTERNAL DOOR.....	21	TECHNICAL DRAWINGS.....	43
WALL MOUNTING BRACKETS.....	23	CUSTOMIZATION = PUNCHING HOLES + LASER.....	47
FLOOR MOUNTING BRACKETS.....	25	WHO WE ARE AND WHAT WE DO.....	49
ROUND POST MOUNTING BRACKETS.....	27		
SQUARED POST MOUNTING BRACKETS.....	28		
CONNECTING FLANGES ( MODULARITY)...	29		
LOCKS.....	33		
VENTILATION DEVICES.....	35		
DOORS.....	37		
ANTI-WIND RETAINER DEVICE.....	38		
LOCKING DEVICE.....	39		
CABLE GLAND.....	40		





# ADVANTAGES AND CHARACTERISTICS

## STANDARDS



Our products are manufactured by the SMC (Sheet Moduling Compound) system, composed by a raw material formed from a resin made of Polyester Reinforced with Fiberglass (GRP).




Double insulating cabinet, material class II , 1000Vac - 1500Vdc.




Excellent cabinets for outside installation and withstanding extreme climate conditions.

Rain, frost, dirt... even chemical agents. They have a much higher lifespan than metallic enclosures.



Manufactured entirely without any metallic parts. WILL NOT RUST



Thermosetting materials do NOT vary in structure or get deformed with climate changes. However, plastic materials WILL get deformed.



Fire resistant at 960°, self-extinguishing material and hallogen free.



IEC-62208 Envelopement with IP66 protection degree against water and dust; non-hygroscopic materials.



High mechanical resistance IK-10 (IEC 62208)



Through IP66 connection flanges, we can achieve enclosures with superior dimensions  
Better handling due to reduced weight, along with easier transportation and storage.



Colour standard RAL7035.



All components made with recyclable materials and reduced waste. Abides by the European restrictions of hazardous residue RoHS



# ADVANTAGES AND CHARACTERISTICS

STANDARDS



Empty enclosures destined to low voltage switchgear and controlgear





## ADVANTAGES AND CHARACTERISTICS

### ANTI-BLOW SYSTEM

Designs with up to 3 or 4 points of pressure. The “wedges” at the door work with the NON-METALLIC system of hinges and press the rubber gasket at the door against the interior of the cabinet, protecting it and guaranteeing the IP66 degree



injected polyurethane  
rubber gasket resistant  
between  $-40^{\circ}\text{C}$ + $60^{\circ}\text{C}$



## ADVANTAGES AND CHARACTERISTICS

NON METALLIC FLEXIBLE POLYAMIDE 6.6 HINGE PINS

NON-METALLIC hinge pins that will prevent any kind of corrosion and rust

Quick, TOOLLESS insertion which allows us to place them and remove them as many times as we want and facilitates working on the door and the cabinet separately

Moreover, the hinge system will remain hidden inside of the cabinet, and its flexibility will prevent the door from breaking

Code	Description	Weight - Kg
ejb-BRES	Hinge pin (2 units)	0,01



180°

Manual installation of the hinge pins, without the need for tools.

The Safybox hinge bolts allow the door to open > 180°



## ADVANTAGES AND CHARACTERISTICS


### ANTI RAIN SHADE



Enclosures are designed with a Shade or Cover which protects the cabinet from getting water inside

This compact and layered cover has the following functions :

- 1.- To avoid water accumulations at the rubber gasket, which due to frost, heat and sudden temperature changes, can be affected once the water has entered.
- 2.- To avoid the water that's accumulated on the roof entering when the door is opened.
- 3.- To avoid the attaching of roofs that can get detached over time.





## ADVANTAGES AND CHARACTERISTICS

### MAXIMUM WATERTIGHTNESS

You'll find in each one of the sides of the cabinet 4 ducts that are independent from the interior compartment, and through which they can simply be secured against a wall without the need of fixing lugs

Other enclosures in the market will need you to DRILL and have the risk of losing watertightness

Our installation doesn't compromise watertightness and maintains the IP66 degree, and moreover we include a bag with all required screws



IP-66








# SAFYBOX BRES BUILDING INSTRUCTIONS

INSERTION OF THE NON-METALLIC HINGE PINS







## ADVANTAGES AND CHARACTERISTICS

NON METALLIC QUARTER TURN 90° LOCK

The standard lock can easily be changed






## SAFYBOX BRES MODEL

EMPTY ENCLOSURE OPAQUE DOOR

Empty enclosures with opaque door • Not mechanized • Double Bar closings  
 INCLUDES: Screwdrivers for direct wall installation ( see pg.22 )



Code	Description	Ht	Wt	Dt	Weight - Kg
BRES-325	Empty cabinet with opaque door	300	250	140	1,93
BRES-43	Empty cabinet with opaque door	400	300	200	3,60
BRES-44	Empty cabinet with opaque door	400	400	200	4,35
BRES-54	Empty cabinet with opaque door	500	400	200	5,25
BRES-64	Empty cabinet with opaque door	600	400	230	7,13
BRES-65	Empty cabinet with opaque door	600	500	230	7,93
BRES-83	Empty cabinet with opaque door	800	300	230	6,40
BRES-86	Empty cabinet with opaque door	800	600	300	12,65

BRES-325



BRES-43



BRES-44



BRES-54



BRES-64



BRES-65



BRES-83



BRES-86






## SAFYBOX BRES Models

EMPTY ENCLOSURE WITH TRANSPARENT WINDOW DOOR


Includes: Empty cabinet • Screwdrivers for wall mounting • Double bar closings  
The window is manufactured with UV protecting transparent polycarbonate



Código	Descripción	Ht	Wt	Dt	Weight - Kg
BRES-325P	Empty cabinet with transparent door	300	250	140	2,00
BRES-43P	Empty cabinet with transparent door	400	300	200	3,57
BRES-44P	Empty cabinet with transparent door	400	400	200	4,30
BRES-54P	Empty cabinet with transparent door	500	400	200	5,21
BRES-64P	Empty cabinet with transparent door	600	400	230	7,05
BRES-65P	Empty cabinet with transparent door	600	500	230	7,56
BRES-83P	Empty cabinet with transparent door	800	300	230	6,40
BRES-86P	Empty cabinet with transparent door	800	600	300	12,15

BRES-64-P






UE

## SAFYBOX BRES-3L MODEL

EMPTY ENCLOSURE WITH TRIPLE LOCK OPAQUE DOOR


INCLUDES: Empty cabinet • Screws for wall mounting • Triple lock with aluminium rods



Code	Description	Ht	Wt	Dt	Weight- Kg
BRES-325-3L	Empty cabinet with triple lock	300	250	140	1,93
BRES-43-3L	Empty cabinet with triple lock	400	300	200	3,60
BRES-44-3L	Empty cabinet with triple lock	400	400	200	4,35
BRES-54-3L	Empty cabinet with triple lock	500	400	200	5,25
BRES-64-3L	Empty cabinet with triple lock	600	400	230	7,13
BRES-65-3L	Empty cabinet with triple lock	600	500	230	7,93
BRES-83-3L	Empty cabinet with triple lock	800	300	230	6,40
BRES-86-3L	Empty cabinet with triple lock	800	600	300	12,65

DOES NOT INCLUDE : European standard brass lock

BRES-65-3L






## SAFYBOX BRES-P-3L MODEL

EMPTY ENCLOSURE WITH TRIPLE LOCK AND TRANSPARENT DOOR

INCLUDES: Empty mechanized cabinet with door with transparent window • Screws for manual installation • Triple lock with aluminium rods and padlock system



Code	Description	Ht	Wt	Dt	Weight - Kg
BRES-325P-3L	cabinet with triple lock and window	300	250	140	2,00
BRES-43P-3L	cabinet with triple lock and window	400	300	200	3,57
BRES-44P-3L	cabinet with triple lock and window	400	400	200	4,30
BRES-54P-3L	cabinet with triple lock and window	500	400	200	5,21
BRES-64P-3L	cabinet with triple lock and window	600	400	230	7,05
BRES-65P-3L	cabinet with triple lock and window	600	500	230	7,56
BRES-83P-3L	cabinet with triple lock and window	800	300	230	6,40
BRES-86P-3L	cabinet with triple lock and window	800	600	300	12,15

DOES NOT INCLUDE : European standard brass lock

BRES-43P-3L






# SAFYBOX BRES HORIZONTAL

EMPTY CABINET IN HORIZONTAL POSITION



INCLUDES: Empty cabinet with downward opening door • EPDM roof and door retainers BO-BRES-RETENE



Code	Description	Ht	Wt	Dt	Weight - Kg
BRES-45	Armario vacío estándar gris RAL7035 Horizontal	400	500	200	5,25
BRES-46	Armario vacío estándar gris RAL7035 Horizontal	400	300	200	7,13
BRES-56	Armario vacío estándar gris RAL7035 Horizontal	500	600	230	7,93
BRES-38	Armario vacío estándar gris RAL7035 Horizontal	300	800	230	6,40
BRES-68	Armario vacío estándar gris RAL7035 Horizontal	300	800	300	12,65

Same advantages as standard BRES cabinets (IP66-IK10)  
New measures gaining space across the width, very necessary for applications such as: photovoltaic, housing batteries ...

It incorporates an EPDM roof at the top of the door.  
Models 38 and 68 are installed with triple individual lock, you can request to adapt other locks to your needs.



## BRES-RETENE

Includes retainer system of the door to cushion the opening downwards at an angle of 145°



BRES-68



BRES-45




# SAFYBOX BRES HORIZONTAL


EMPTY CABINET IN HORIZONTAL POSITION




BRES-45




BRES-46




BRES-56



BRES-38



BRES-68







## SAFYBOX BRES ACCESSORIES


### 3mm POLYESTER BACK PANNEL

DOES NOT INCLUDE: fastening screws for the M6x10 cabinet ( since they're already included with the cabinet)

Code	Description	Ht	Wt	Dt	Weight - Kg
PBP-325	Polyester back pannel for the BRES-325 model	262	198	3	0,38
PBP-43	Polyester back pannel for the BRES-43 model	360	248	3	0,59
PBP-44	Polyester back pannel for the BRES-44 model	360	348	3	0,87
PBP-54	Polyester back pannel for the BRES-54 model	460	348	3	1,09
PBP-64	Polyester back pannel for the BRES-64 model	558	348	3	1,30
PBP-65	Polyester back pannel for the BRES-65 model	558	448	3	1,75
PBP-83	Polyester back pannel for the BRES-83 model	756	248	3	1,46
PBP-86	Polyester back pannel for the BRES-86 model	756	548	4	2,78

⚠ Back pannel with centered mechanizations for an extra anchoring of up to 1-2 and even 3 attachments

Prevents the base from sagging when placing heavier components, improves the stiffness of the plate (request for extra screws)






## SAFYBOX BRES ACCESSORIES

### 2mm METALLIC BACK PANNEL

Manufactured with galvanized white back panel

DOES NOT INCLUDE : fixing screws for the M6x10 cabinet (since they're already included with each cabinet)

Code	Description	Ht	Wt	Dt	Weight- Kg
PBM-325	Metallic back pannel for the BRES-325 model	262	198	2	0,79
PBM-43	Metallic back pannel for the BRES-43 model	360	248	2	1,30
PBM-44	Metallic back pannel for the BRES-44 model	360	348	2	1,90
PBM-54	Metallic back pannel for the BRES-54 model	460	348	2	2,20
PBM-64	Metallic back pannel for the BRES-64 model	558	348	2	3,00
PBM-65	Metallic back pannel for the BRES-65 model	558	448	2	3,60
PBM-83	Metallic back pannel for the BRES-83 model	756	248	2	3,26
PBM-86	Metallic back pannel for the BRES-86 model	756	548	2	6,40





## SAFYBOX BRES ACCESSORIES

CHASSIS FOR MODULAR SWITCHGEAR ( 17,5 mm)

Complete set of metallic chassis, DIN rails and mechanized polycarbonate plate.  
DOES NOT INCLUDE: cabinet

Code	Description	Weight- Kg
CHM-325	Capacity for 20 modules, with BRES-325 (2 rows)	1,15
CHM-43	Capacity for 24 modules, with BRES-43 (2 rows)	1,22
CHM-44	Capacity for 36 modules, with BRES-44 (2 rows)	1,50
CHM-54	Capacity for 54 modules, with BRES-54 (3 rows)	1,80
CHM-64	Capacity for 72 modules, with BRES-64 (4 rows)	2,32
CHM-65	Capacity for 96 modules, with BRES-65 (4 rows)	2,62
CHM-83	Capacity for 70 modules, with BRES-83 (5 rows)	2,22
CHM-86	Capacity for 145 modules, with BRES-86 (5 rows)	4,37
TEX-18	18 mm removable cover. for unused modules	0,05

BRES-43 + CHM-43







# SAFYBOX BRES ACCESSORIES


## INSTRUCTIONS FOR CHASSIS ASSEMBLY



- 1 Place the 4 m6x20 raisers on the bottom to supplement the chassis




- 2 Use your hand to insert the black raisers on top of the "l" shaped outline, if you want to reinforce it, you can tighten it against the outline with the provided screws




- 3 Hold the L shaped outline over the raisers (don't completely tighten the corners)

- 4 Place the DIN rails at the desired location and... now finally !! ...tighten the screws at the corners as much as you can



- 5 Finally, place the protection plate and attach it using the provided screws






# SAFYBOX BRES ACCESSORIES

## INTERNAL DOORS



Interior door with double bar closing (includes all necessary accessories for assembly). Does not include the cabinet




Code	Description	Ht	Wt	Useable depth	Weight - Kg
PUI-325	Internal polyester door for BRES-325	280	230	72	0,45
PUI-43	Internal polyester door for BRES-43	380	280	132	0,55
PUI-44	Internal polyester door for BRES-44	380	380	132	0,65
PUI-54	Internal polyester door for BRES-54	480	380	132	0,75
PUI-64	Internal polyester door for BRES-64	580	380	132	0,85
PUI-65	Internal polyester door for BRES-65	580	480	132	0,95
PUI-83	Internal polyester door for BRES-83	780	280	132	1,10
PUI-86	Internal polyester door for BRES-86	780	580	232	2,0

⚠ The internal doors have a single double bar lock, the same as the cabinet and its handle, but you may request a different type of lock



BRES-44 + PUI-44





## SAFYBOX BRES ACCESSORIES

ASSEMBLY INSTRUCTIONS FOR INTERNAL DOORS




- 1 Place the provided NIR-511 inserts on the square-shaped hubs




- 2 Chose the aperture side for the door and place the provided hinges, strapping them with the m6x10 screw

The hinge bolt will remain towards the exterior side of the cabinet



- 3 On the opposite side perform the same operation with the door's supporting piece



- 4 Finally, insert the door in the hinge and pass the closing pins through the door and the hinge (in both sides)







## SAFYBOX BRES ACCESSORIES


### DIRECT WALL MOUNTING - FIXING LUGS

We recommend strapping directly to the wall in order to avoid breaking the IP-66 degree  
Each cabinet includes a bag with screws for the back panel, double bar key, and  
plugs+screws for a DIRECT wall mounting

Code	Description	Weight - Kg
OFM-14	Wall fixing lug with interior fixing screw (4 un. bundle)	0,09
OFM-14-B	Wall fixing lug with exterior fixing screw (4 un. bundle)	0,09
OFM-14-F	Post fixing lug through straps (4 un. bundle)	0,09

! We offer OFM-14 lugs but because of their design you don't actually need them....you can spare them !!






## SAFYBOX BRES ACCESSORIES

DIRECT WALL MOUNTING - PREMARKED DISTANCES




All cabinets are premarked on their posterior area with the measurements between the direct wall attachment points




Code	Description	Ht	Wt	Dt	H	W
BRES-325	Empty standard cabinet	300	250	140	250	223
BRES-43	Empty standard cabinet	400	300	200	348	273
BRES-44	Empty standard cabinet	400	400	200	348	373
BRES-54	Empty standard cabinet	500	400	200	448	373
BRES-64	Empty standard cabinet	600	400	230	546	373
BRES-65	Empty standard cabinet	600	500	230	546	473
BRES-83	Empty standard cabinet	800	300	230	748	273
BRES-86	Empty standard cabinet	800	600	300	744	573

! Therefore you don't need to raise up the cabinet to mark the distances








## SAFYBOX BRES ACCESSORIES

FLOOR MOUNTING : PEDESTALS AND SOCLES




They allow the BRES cabinet to be placed on the floor, various lock possibilities (upon inquiry)



Code	Description	Ht	Wt	Dt	Weight - Kg
F0-44	Socle for BRES-44	500	365	170	6,1
F1-44	Socle for BRES-44	750	365	170	7,9
F2-44	Socle for BRES-44	1000	365	170	8,85
F0-54	Socle for BRES-54	500	365	170	6,1
F1-54	Socle for BRES-54	750	365	170	7,9
F2-54	Socle for BRES-54	1000	365	170	8,85
F0-64	Socle for BRES-64	500	365	200	6,15
F1-64	Socle for BRES-64	750	365	200	7,95
F2-64	Socle for BRES-64	1000	365	200	8,9
F0-65	Socle for BRES-65	500	465	200	7,2
F1-65	Socle for BRES-65	750	465	200	8,9
F2-65	Socle for BRES-65	1000	465	200	9,9
F0-86	Socle for BRES-86	500	500	300	8,25
F1-86	Socle for BRES-86	750	500	300	10,1
F2-86	Socle for BRES-86	1000	500	300	11



BRES-44-3L + F1-44




## SAFYBOX BRES ACCESSORIES

FLOOR MOUNTING : PEDESTALS AND SOCLES



It's necessary to mechanize the enclosure to install the socle.

BRES-65-3L + F1-65 ( custom model with padlock and support pannel)





# SAFYBOX BRES ACCESSORIES


POLE MOUNTING : ROUND POLE



Clamping set for fixing the cabinet to round posts  
INCLUDES: Stainless steel support and strap

Code	Description	(Lg)	(Fd)	Weight - Kg
SOP-POST-X3	set clamping profiles BRES-43	300	20	0,36
SOP-POST-X4	set clamping profiles BRES-44	400	20	0,48
SOP-POST-X5	set clamping profiles BRES-54	500	20	0,59
SOP-POST-X6	set clamping profiles BRES-64	600	20	0,700

screw installation details



X3



X4



X5



X6



raw material :  
Galvanized metal frame



## SAFYBOX BRES ACCESSORIES


### SQUARED POST MOUNTING



Lugs for the 16 mm strap, designed to attach the cabinet to squared posts, made with polyamide 6.6

INCLUDES : 4 unit set

DOES NOT INCLUDE : Strap (maximum recommended size 16mm x 2mm)




ⓘ Minimum width recommended for post fixing 250mm





# SAFYBOX BRES ACCESSORIES


IP-66 CONNECTION FLANGES






# SAFYBOX BRES ACCESSORIES

## CONNECTION FLANGES ASSEMBLY MANUAL




1



You must drill both cabinets to join them

2




narrow side


Place the connection flange between both cabinets so it may be used as template

thick side

3



Strap using the provided m8 x 30 screws






# SAFYBOX BRES ACCESSORIES



## IP-66 UNION FLANGES

Allow two cabinets to be attached together, maintaining IP-66 in VERTICAL UNIONS

Code	Description	Weight - Kg
UA-230X100	Connection flange through the upper and lower sides for BRES-325 y BRES-43 (A)	0,15
UA-350X150	Connection flange through the upper and lower sides for BRES-44, BRES-54, BRES-64, BRES-65, BRES-83 y BRES-86 (B)	0,19
UA-350X150-B	Connection flange VERTICAL+HORIZONTAL BRES-83 y BRES-86 (C)	0,24







# SAFYBOX BRES ACCESSORIES


IP-66 CONNECTION FLANGES



HORIZONTAL + VERTICAL cabinet DETAIL



BRES-325 + BRES-43







# SAFYBOX BRES ACCESSORIES


22mm LOCKS WITH MECHANIZATION



Locks + key to place inside the BRES cabinet. All of them have a sealable thread mechanism. Request one unit for the BRES-325 model; for all others, 2 units per cabinet will be necessary

Code	Description		Weight - Kg
CCU-08	8 mm squared lock	(A)	0,05
CDB-10	Double bar lock (STANDARD)	(B)	0,04
CTR-11	11 mm triangular lock	(C)	0,04
CML-12	Lock with manual handle and key	(D)	0,07
LLD-10	Double bar key		0,01

(B)



(D)



! The lock can also be used as handle when turned 90 degrees.

The key is standard model n.1333  
Other key models can be requested.



- CDB-10 Double bar 10 mm dim
- CTR-11 Triangular 11 mm side
- CCU-08 Squared 8 mm side
- TPA-APM ALLEN brass male 5 mm
- TPAC-APM Brass squared female 8 mm
- TPAI-APM Brass hexagonal female 6 mm




## SAFYBOX BRES ACCESSORIES


### TRIPLE LOCK RODS



cabinets with optional triple lock via lever and stainless steel bolt, in order to place a padlock



ⓘ Thanks to its premarked interiors, we simplify any switch and button installation



ⓘ The ZIG-ZAG design throughout the inside of the doors gives them a higher mechanical resistance and prevents any arching that may be caused by temperature changes



# SAFYBOX BRES ACCESSORIES

## Ip54 VENTILATION DEVICES



Allows the entry and natural circulation of air, we recommend 2 units per cabinet in a diagonal position.

Code	Description	Weight - Kg
DV-M	Ventilation system (IP-54)	0,01
DV-G	Large ventilation system (IP-54)	0,03
DV-IP66	Large ventilation system (IP-66)	0,03

⚠ It's necessary to mechanize the cabinet in order to perform the installation (In some models, it will reduce the protection of the cabinet to IP54)

DV-M







Diagram of the DV-m machining





# SAFYBOX BRES ACCESSORIES

IP54 VENTILATION DEVICES

The LARGE device has a rubber membrane for the IP-54 protection, we recommend the use of 2 units

DV-G






Diagram of the DV-g machining





# SAFYBOX BRES ACCESSORIES

## SPARE DOORS



Opaque door • Not machined

INCLUDES : Double bar locks • hinge pins

Code	Description	Ht	Wt	Weight - Kg
PUB-325	Opaque door for bres-325	300	250	0,610
PUB-43	Opaque door for bres-43	400	300	0,850
PUB-44	Opaque door for bres-44	400	400	1,253
PUB-54	Opaque door for bres-54	500	400	1,511
PUB-64	Opaque door for bres-64	600	400	1,728
PUB-65	Opaque door for bres-65	600	500	2,086
PUB-83	Opaque door for bres-83	800	300	1,862
PUB-86	Opaque door for bres-86	800	600	3,508

Machined door with transparent window • Polycarbonate cover with UV protection

INCLUDES: Double bar locks • hinge pins

Code	Description	window dimension			Weight - Kg
		Ht	Wt	rd	
PUB-325P	Windowed door for bres-325	200	80	25	0,610
PUB-43P	Windowed door for bres-43	280	120	25	0,850
PUB-44P	Windowed door for bres-44	280	220	30	1,253
PUB-54P	Windowed door for bres-54	380	220	30	1,511
PUB-64P	Windowed door for bres-64	480	220	30	1,728
PUB-65P	Windowed door for bres-65	480	320	35	2,086
PUB-83P	Windowed door for bres-83	600	120	25	1,862
PUB-86P	Windowed door for bres-86	600	400	35	3,508



! The ZiG-ZAG design throughout the inside of the doors gives them a higher mechanical resistance and prevents any arching that may be caused by temperature changes



## SAFYBOX BRES ACCESSORIES


### DOOR HOLDERS


2 HOLDERS to prevent the doors and the hinges from breaking. They will absorb any air bursts, impacts during manipulation and installation of the systems...

Code	Description	Weight - Kg
BO-BRES-RETENE	Holders for the entire range of BRES cabinets (2 un)	0,01

Complete self-assembly set :  
INCLUDES: 2 Holders, 4 m6x10 screws y 4 M6 inserts

Install this accesorie limits 145° door opening







# SAFYBOX BRES ACCESSORIES

## PADLOCK DEVICES



Padlocking devices for manual installation on the lock itself, the lock must be dismantled for the installation

Code	Description	Weight - Kg
CBC-13-IN	Lock for securing a padlock device, STAINLESS steel (1 un)	0,12
CBC-13	Lock for securing a padlock device, bichromate steel (1 un)	0,10



BRES-43P





## SAFYBOX BRES ACCESSORIES

### Ip67 CABLE GLANDS



If you'd like, we can also customize the cabinet for you  
(round, squared, even countersunk machinings)

Code	Metric	cable section - MIN		MAX	diameter	dim-machinings	Weight - Kg
PG-7	M-12	2,5	6,5		9	12,5	0,01
PG-9	M-16	4,5	8		9	15,5	0,01
PG-11	M-20	5	10		9	18,6	0,01
PG-13,5	M-20	6	12		10	20,4	0,02
PG-16	M-25	7	14		10	22,5	0,02
PG-21	M-32	11	18		12	28,3	0,02
PG-29	M-40	17	25		13	37	0,03
PG-36	M-50	22	32		16	47	0,03
PG-42	M-50	26	39		17	54	0,03
PG-48	M-63	30	44		18	59,3	0,04

## MACHINING

We customize the cabinets in our completely automated 3D printer departments

We can customize any of the sides of the cabinet, backside, sides, door, etc...

Our custom cabinet solutions are panel builder friendly, ready for direct assembly and avoid requiring manual machining, which can often be inaccurate or inefficient.

## LASER MARKINGS

Forget about tags always getting lost or disappearing.

We can use lasers to mark directly over our cabinets the logo of your company, corporate image or QR/VIDI code.







# PACKING SAFYBOX BRES

UNITS PER PALLET AND THE 20 AND 40 FEET CONTAINERS



270  
Units

119  
Units

85  
Units

66  
Units

47  
Units

43  
Units


18  
Units



20' CONTAINER

115 cms extra width

160 cms extra length



7

pallets in the 20' container

40' CONTAINER




15

pallets in the 40' container



# SAFYBOX BRES GENERAL DATA TABLE



	BRES-325	BRES-43	BRES-44	BRES-54	BRES-64	BRES-65	BRES-83	BRES-86
<b>Exterior Dimensions</b>								
Height (mm)	300	400	400	500	600	600	800	800
Width (mm)	250	300	400	400	400	500	300	600
Depth (mm)	140	200	200	200	230	230	230	300
<b>Usable Interior Dimensions</b>								
Height (mm)	273	373	373	473	573	573	773	773
Width (mm)	207	257	357	357	357	457	257	557
Depth (mm)	123	183	183	183	213	213	213	283
<b>Packing</b>								
Un/Palet 155x110cm	270	119	85	66	47	43	56	18
Un/Palet 110x110cm	208	84	60	50	40	32	32	12
Un/Palet 120x80cm	130	66	54	44	32	24	30	12
Un/Container 20' ( 11 pallets 120 x 80 x 220 cm)	1.430	726	594	484	352	264	330	132
Un/Container 40' ( 25 pallets 120 x 80 x 220 cm)	3.250	1.650	1.350	1100	800	600	750	300
<b>Other characteristics</b>								
N. of locks	1	2	2	2	2	2	2	2
N. of anti-buckling systems	1	2	2	2	2	2	2	2
Plate attachment points	4	4+1	4+1	4+2	4+2	4+2	4	4+3
Dissipation DT=40°C (W)	36,20	58,80	72,60	82,90	99,40	117,00	103,00	185,00
Weight (kg)	1,93	3,60	4,35	5,25	7,13	7,93	6,40	12,65
<b>Polyester plate</b>								
	pbp-325	pbp-43	pbp-44	pbp-54	pbp-64	pbp-65	pbp-83	pbp-86
Height (mm)	262	360	460	560	558	558	756	756
Width (mm)	198	248	348	348	348	448	248	548
Thickness (mm)	3	3	3	3	3	3	3	4
Weight (kg)	0,38	0,59	0,87	1,09	1,30	1,75	1,46	2,78
<b>Metallic plate</b>								
	pbm-325	pbm-43	pbm-44	pbm-54	pbm-64	pbm-65	pbm-83	pbm-86
Height (mm)	262	360	460	560	558	558	756	756
Width (mm)	198	248	348	348	348	448	248	548
Thickness (mm)	2	2	2	2	2	2	2	2
Weight (kg)	0,79	1,30	1,90	2,20	3,00	3,60	3,26	6,40
<b>Internal door</b>								
	PUI-325	PUI-43	PUI-44	PUI-54	PUI-64	PUI-65	PUI-83	PUI-86
Height (mm)	280	380	380	480	580	580	780	780
Width (mm)	230	280	380	380	380	480	280	580
Depth (mm)	17	17	17	17	17	17	17	17
Weight (kg)	0,49	0,59	0,75	1,00	1,10	1,30	1,10	2,20
<b>DIN Rail chassis</b>								
	CHM-325	CHM-43	CHM-44	CHM-54	CHM-64	CHM-65	CHM-83	CHM-86
Height (mm)	270	365	365	465	565	565	765	765
Width (mm)	226	278	378	378	378	478	278	578
Depth (mm)	110	125	125	125	125	125	125	125
Module capacity	20	24	36	54	72	96	70	145
<b>Socle 500mm height, Weight (kg)</b>			F0-44 (6,10)	F0-54 (6,10)	F0-64 (6,10)	F0-65 (7,20)	F0-86 (8,25)	
<b>Socle 750mm height, Weight (kg)</b>			F1-44 (7,90)	F1-54 (7,90)	F1-64 (7,90)	F1-65 (8,90)	F1-86 (10,10)	
<b>Socle 1.000mm height, Weight (kg)</b>			F2-44 (8,85)	F2-54 (8,85)	F2-64 (8,85)	F2-65 (9,90)	F2-86 (11,00)	




depth 140 mm

# SAFYBOX BRES RANGE

INTERNAL AND EXTERNAL DIMENSIONS




## BRES-325




depth 200 mm


## BRES-43



## BRES-44



## BRES-54







depth 230 mm  
BRES-64

# SAFYBOX BRES RANGE


INTERNAL AND EXTERNAL DIMENSIONS




BRES-65



BRES-83



BRES-86



depth 300 mm





# SAFYBOX BRES RANGE



INTERNAL AND EXTERNAL DIMENSIONS





### BRES-325





### BRES-43



### BRES-44



### BRES-54







# SAFYBOX BRES RANGE

## INTERNAL AND EXTERNAL DIMENSIONS


### BRES-64




### BRES-65



### BRES-83



### BRES-86





CUSTOM DIVISION

ALARMA



MARCHA

PROTECCION  
MOTOR DISPARADA

MARCHA

PROTECCION  
MOTOR DISPARADA



BOMBA  
AUT. - 0 - MAN



BOMBA  
AUT. - 0 - MAN



SILENCIADO SRENA  
0 1



INTERRUPTOR  
PRINCIPAL  
SEMPRE ARRANCA EM POSICAO 1



URIARTE SAFYBOX   
[www.safybox.com](http://www.safybox.com)



# choose your degree of customization

choose your enclosure model



empty box

customized box

fully equipped box



Do it yourself

We can do the holes

We can fully equip them

We can also laser-mark your logo







# Who are we ?

The URIARTE group is specialized in offering energy related solutions, with its headquarters located in Bilbao (Spain), it manufactures its products in Europe for the different electric, gas, water, and telecommunications sectors. With production centers in Spain, Poland and Portugal, and sales offices in the United Kingdom and Equatorial Guinea, the group has more than 60 years of experience, providing our clients with outstanding quality and adaptability.

We export to 68 countries worldwide. Our potential clients tend to be electric, water, gas or telecommunications companies, and distribution, warehousing, engineering, construction and installation companies.

In our three production facilities, we have 35 large tonnage pressing machines, 24 thermoplastic injection machines, 3D robots, laser printing machines, robotized gasket system, etc. We have a production capability of 10,000 units per day.

But above all, our team will always be happy to serve you in an efficient and unique way!



# What do we do ?

We manufacture both empty and fully equipped enclosures, in accordance with the most demanding characteristics, we can customize any aspect of the enclosure, such as modularity, mechanization, logo laser printing, colors, equipment installation, locking systems, and other accessories.

